Product data sheet



Product description

Area **Crimpcontact**Part no. **Crimpcontact**65 0797 098 01

Illustration



Technical data

General features

Part no.	65 0797 098 01
Version	Socket contact
Cross-sectional area	0.35-0.50 mm ²
Packaging type	Strip (200 pcs.)
Crimp dimensions (guide value)	0.35 mm ² : 0.93-1.1 mm - 0.50 mm ² : 0.95-1.12 mm
Crimp pullout force	0.35 mm ² : 53 N - 0.50 mm ² : 73 N
Weight (g)	71.85
Customs tariff number	74093900
Country of Origin	DE

Material

Contact material	CuSn (bronze)
Contact plating	Au (gold)
REACH SVHC	None (No pollutants)
SCIP number	SCIP-number not available

Classifications

eCl@ss 11.1	27-46-04-03

Product data sheet



Product description

Area **Crimpcontact**Part no. **Crimpcontact 65 0797 098 01**

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".